

Drytec Filtros de linha

Modelo	Capacidade			Entrada	Dimensões(mm)			Peso Kg	Tipo de elemento
	m³/h	m³/min	scfm		Diametro	Altura	Manom.		
G25X	25	0,42	14,8	1/4"	102	219,5	45	1,35	M25X
G25Y									M25Y
G25A									M25A
G50X	50	0,83	29,5	3/8"	102	219,5	45	1,35	M50X
G50Y									M50Y
G50A									M50A
G100X	100	1,67	59,0	1/2"	102	257,5	45	1,51	M100X
G100Y									M100Y
G100A									M100A
G150X	150	2,50	88,5	3/4"	123	302,5	45	2,27	M150X
G150Y									M150Y
G150A									M150A
G200X	200	3,30	118,0	3/4"	123	366,5	45	2,55	M200X
G200Y									M200Y
G200A									M200A
G250X	250	4,17	147,5	1"	123	406,5	45	2,89	M250X
G250Y									M250Y
G250A									M250A
G300X	300	5,00	177,0	1 1/4"	123	463,0	45	3,18	M300X
G300Y									M300Y
G300A									M300A
G500X	500	8,33	295,0	1 1/4"	123	493,0	45	3,37	M500X
G500Y									M500Y
G500A									M500A
G600X	600	10,00	354,0	1 1/2"	123	538,0	45	3,69	M600X
G600Y									M600Y
G600A									M600A
G851X	851	14,18	502,1	2"	160	625,5	45	5,61	M851X
G851Y									M851Y
G851A									M851A
G1210X	1210	20,17	713,9	2"	160	695,5	45	5,98	M1210X
G1210Y									M1210Y
G1210A									M1210A
G1520X	1520	25,33	896,8	2 1/2"	230	592,0	45	10,70	M1520X
G1520Y									M1520Y
G1520A									M1520A
G1820X	1820	30,33	1073,8	3"	230	701,5	45	11,33	M1820X
G1820Y									M1820Y
G1820A									M1820A

Fator de correção para secadores da série SD

Pressão(bar)	4	6	7	8	10	12	16
F1	0,76	0,92	1,00	1,07	1,19	1,31	1,51

